



General measurements from the bottom of the door for standard 2040mm doors:

- Eye viewer height - 1450mm
- Roller night latch height - 1100mm
- Lever height - 1020mm
- Cylinder height for dead locks - 1020mm
- Disabled WC lever height - 920mm
- Disabled additional eye viewer - 1050mm

Non standard height doors - positions as above or mid height as appropriate. Other ironmongery as appropriate unless specified in advance by the customer

Height to bottom of pull handles:

- 225mm handle - 1030mm
- 300mm handle - 960mm
- 425mm handle - 835mm

Height to bottom of pull handles on door fitted with lock:

- 225mm handle - 1080mm

Kick plate sizes:

- 926mm doors = 886 x 150mm
- 826mm doors = 786 x 150mm

Giving approx 10mm margin between the door stops and the edge of the kick plate and 5mm margin between the kick plate and the bottom of the door.

Do Not Scale.

Description: Standard metric ironmongery positions



Unit 6, Ranskill Court,  
Sheffield,  
S9 5FZ.

Size: 2040 x 926mm Door  
Tolerance: +/- 0.5mm  
Fire Rating: N/A

Drawn By: P. Brash  
Approved: Approved

Drawing No: DP16658  
Revision: 01  
Drawn Date: 15/01/2020

©Doorpac Limited  
All Dimensions Are  
In mm Unless Stated.

If In Doubt Ask!