

Technical Data Sheet TL Range of Laminate Doors



Satin White



Mid Grey



Light Grey



Dark Grey Woodgrain



Dark Brown Woodgrain



Light Grey Woodgrain



Walnut Woodgrain

Product Reference: TL Range of Laminate Doors

Door Facings: Thin CPL Laminate

Available in over eighty woodgrains and over fifty plain

colours

Light and Deep Embossed finishes also available

Door Core: Multi-layer Particleboard Core (E1 compliant)

Door Lippings: Concealed. Minimum 6mm to all edges in Hardwood.

Door edges can also be edge-banded to match the face

Fire Resistance: FD30 – Certifire Certificate CF5228

FD60 – Certifire Certificate CF5229

Also available as FD90 and FD120 Doorsets

Chain of Custody: FSC Chain of Custody



Technical Data Sheet TL Range of Laminate Doors

TL Range of Laminate Doors				
	35mm	44mm	44mm	54mm
	Solid Core	Solid Core	FD30	FD60
Single Leaf Size (Max) ¹		1000x3300mm	915x3000mm	1000x3000mm
	926x2150mm	Or	Or	Or
		1220x2440mm	1165x2440mm	1220x2440mm
Paired Leaf Size (Max)		1000x3300mm	1000x2942mm	936x3000mm
	926x2150mm (2)	Or	or	Or
		1220x2440mm	1165x2440mm	1106x2440mm
		(2)	(2)	(3)
Door Weight (Nominal)	19Kg/m2	27Kg/m2	27Kg/m2	34Kg/m2
Aperture Area (Max)	No	No	1.51m2	1.12m2
	Restriction	Restriction		
Aperture Height(Max)	No	No	2085mm	2201mm
	Restriction	Restriction	(at 725mm wide)	(at 510mm)
Aperture Width (Max)	No	No	822mm	604mm
	Restriction	Restriction	(at 1840mm High)	(at 1860mm)
Margin to Edge of	100mm	100mm	100mm	120mm
Door (Min)				
Margin between	100mm	100mm	100mm	120mm
Apertures (Min)				
Acoustic Performance	N/A	32dB	32dB	35dB
(Max)				
PAS24 Doorsets	-	-	Yes	Yes

 $^{^{(1)}}$ — Unlatched and Latched, Single Acting Single Leaf

 $^{^{(2)}}$ — Unlatched and Latched, Single Acting Paired Leafs

 $^{^{(3)}}$ — Latched, Single Acting Paired Leafs